

Highway Maintenance Safetrack® LM Product in Action

High Performance Cold Plastic Line Marking Systems SAFETY WITHOUT COMPROMISE



Ref. PIA_Safe016(5E).pdf Available from stirlinglloyd.com



STIRLING LLOYD UK & WORLD WIDE Stirling Lloyd Polychem Ltd. Union Bank . King Street . Knutsford Cheshire . WA16 6EF . UK Tel: +44 (0) 1565 6335111 Fax: +44 (0) 1565 633555 Email: marketing@stirlinglloyd.com STIRLING LLOYD NORTH AMERICA Stirling Lloyd Products Inc. 152 Rockwell Road . Building A Newington . CT 06111 . USA Tel: +1 860-666-5008 Fax: +1 860-666-5106 Email: northamerica@stirlinglloyd.com



www.stirlinglloyd.com

Copyright © 2011 | Stirling Lloyd Polychem Ltd.

www.highwaymaintenanceproducts.com

High Perfomance Road Maintenance Systems

The Safetrack LM range offers a number of benefits over thermoplastic line marking products:

- Far longer service life with minimal degradation in luminance and colour.
- Superior dry night and wet night retroreflectivity.
- Better bead retention.
- Improved skid resistance.
- Greater temperature tolerance and thermal stability.
- Superior adhesion to a wide range of substrates.

- Improves long term road safety and site safety (no hot trades).
- Reduced environmental impact.
- Longer service life reducing lane closures, easing congestion and reducing pollution.
- Large reduction in maintenance and whole life cycle costs, providing "best value".

Performance Chart	Retromax		Durable	
Dry Retroreflectivity (mcd/m²/lx)	355	R5	N/A	N/A
Wet Retroreflectivity (mcd/m²/lx)	55	RW3	N/A	N/A
Skid Resistance (SRT)	55	S3	60	S4
Luminance Coefficient (Qd)	195	Q3	197	Q3

Accelerated wear tests after 3,500,000 wheel overs

Areas of Use	Retromax	Durable
Motorways & 'A' Roads - Guide & Centre Lines	-	
Markings at Junction - e.g. Stop Lines		
Minor Roads		
Direction Arrows		
Yellow Lines		
Roads with Street Lighting		
Airfields		
Car Parks		
Cycle Lanes / Bus Lanes / Restricted Areas		
Pedestrian Crossings		
Warehouses (Internal Applications)		

Safetrack LM Retromax is available in standard **white** and **yellow**, while Durable is available in standard **white**, **yellow**, **red** and **black**. Stirling Lloyd can also manufacture these systems in virtually any colour to meet your specification.



www.stirlinglloyd.com

STIRLING LLOYD UK & WORLD WIDE

Stirling Lloyd Polychem Ltd. Union Bank . King Street . Knutsford Cheshire . WA16 6EF . UK Tel: +44 (0) 1565 633111 Fax: +44 (0) 1565 633555 Email: marketing@stirlinglloyd.com

STIRLING LLOYD NORTH AMERICA www.northamerica.stirlinglloyd.com

The information contained in this literature is accurate to the best of the publisher's knowledge and we reserve the right to alter any of the details contained herein without notice. It must not be taken in any way to form a specification and Stirling Lloyd accepts no liability whatsoever arising out of the use of the information contained herein. This documentation does not form part of the 'Conditions of Sale' of our products. Ref. PIA_Safe016(5E).pdf Available frolm stirlinglloyd.com



Copyright © 2011 | Stirling Lloyd Polychem Ltd.